



NOTES:
1) MATERIAL: 6061-T6/T62/T6510/T6511 SEAMLESS TUBING
PER WW-T-700/6
OR QQ-A-200/8 OR QQ-A-225/8
OR AMS 4080 OR AMS 4082 OR AMS 4083
OR ASTM B210 OR ASTM B241
REF DART SPEC M6061T6T1.500W0.120
2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: IDENTIFY PER DART SPEC QSI 044 6.1
7) WEIGHT: 0.59 lbs
8) NO CRUSHING IN HATCHED AREA

D5627-1 TUBE

RELEASED

2018 JUL 30 NO
ECN 18-749

APPROVED

B	REVISED TUBE LENGTH (ZND4-1)	VS	18.05.23
A	NEW ISSUE	VS	18.03.06
REV.	DESCRIPTION	BY	DATE
DESIGN	VS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	VS		
CHECKED	RF	DRAWING NO.	REV. B
MFG. APPR.	DD	D5627	SHEET 1 OF 1
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	TUBE	NTS
DATE	18.05.23	COPYRIGHT © 2018 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	